


iFollow, a new iSolution member, comes with versatile functions for stage and theatre applications. Featuring color wheel, color temperature filters 3200K, 5600K, and 6000K, auto focus, 100% dimmer, shutter, iris, etc., the powerful Follow Spots are ideal for highlighting the figures on the stage.



IF-ST, Stand (Option)



IF-1200

- DMX 512 control channels : 6 channels
- Custom-designed iLead controller or universal DMX controllers.
- Setting and addressing : 4 digit blue LED display. LED display with on/off setting function.
- Data in/out : Locking 5-pin XLR

Controller

- A professional, user friendly DMX 6 Ch. Controller for follow spot.
- Equipped with 9 different hold-color buttons for instant access of colors.
- Slide control the shutter, Iris, Color, Color temperature, Dimmer and focus, rapid and convenient.

Iris:

- Motorized iris for different beam diameters.

Color wheel:

- 8 dichroic colors plus white.
- Rainbow effect in both directions.

Effect Wheel:

- With color temperature filter 3200K, 5600K, and 6000K plus open, combined with color wheel produce 27 colors effects.

Dimmer/ Shutter

- 0 ~ 100% dimmer.
- Independent shutter/ variable speed strobe.

Focus:

- Automatic focus by DMX control

Optics:

- High efficiency optical system.
- High quality optical lens and dichroic colors.
- Beam angle :13°

Construction:

- Stylish housing.
- With ultra-smooth, micro-stepping motors.
- Easy handle, follow the focal point easily.

Electrical and Specification:

- Power supply:230V 50Hz(IF-1200)
- Bulb : HMI 1200W
- Size : 1170 x 330 x 225 mm, Controller 405 x 360 x 35 mm
- Weight: 44 kgs(IF-1200)



DMX-512 Configuration

Channel 1	Channel 2	Channel 3	Channel 4	Channel 5	Channel 6
Shutter	Iris	Color	Color Temperature	Dimmer	Focus
248-255 Open 247 Fast shutter 016 Slow shutter 008-015 Open 000-007 Blackout	255 Min. 0 Max.	255 Fast 192 Slow 191 Slow 128 Fast 113-127 Pink 098-112 UV purple 085-098 Light blue 071-084 Orange 057-070 Green 043-056 Magenta 029-042 Yellow 016-028 Red 000-014 White	171-255 3200K 086-170 5600K 000-085 6000K	255 100% 000 0%	255 0

FCF-1200

- Size: L 122 x W 52.5 x H 49 cm
- Weight:46.8kgs

IF-1200/FC

- Per package with 1pc of IF-1200
- Weight:94.8kgs